ArteVino

OFIGINE BVCert. 6010761

multi-temperatures cabinet with a temperature staggering from



EAN Code : 3543290003681

CONFIGURATION	Storage shelves	Sliding shelves	Capacity**
Maximum Configuration (100% sliding)	-	13	170
Mixed Configuration	2	4	206
Minimum Configuration (100% storage)	4	0	230
Standard Configuration	5	-	225

UNIVERSAL SHELF

Universal shelf: AOHUI Weight: 2.6 kg Type of structure: slats Number of bottles per level: 12

Material: Solid Beechwood coated with an ecological water varnish.

AOHUI shelf is universal. It can be positioned in



Single Solid beechwood universal shelf	AOI	HUI 3543290002783	

- Standard configuration
- Traditional Bordeaux bottles
- Calculated with an ambient temperature of 25°C
- **** Consumption calculated with an ambient temperature of 25°C using an appliance with standard configuration
- R600a gas. With a R134a gas (for US, CA, Korea, Taïwan): 38 db(A)

Range : OXYGEN Model OXGMT225NVD Fonction : Service Capacity* : 225 Bottles** A constant temperature due to the dual Heating/Cooling controls.



Optimised humidity due to the circulation of humid air.

Air circulation ensured by a breather hole located inside the cellar.

No vibration thanks to the slow-cycles compressor fixed on silentblocs + evaporator flooded in the high density polyurethane foam.

Protection from UV light guaranteed with a glass door with highly effective UV filter.

« Storage and/or sliding » universal shelf. One shelf for all types of storages. Suitable to store all types of bottles.

GENERAL FEATURES

Gross weight, packaged(kg)* Net weight (kg)* Dimensions in packaging H x W x D (mm) Dimensions H x W x D (mm)	: : :	5 99 950 x 720 x 760 825 x 680 x 690
Color scheme	:	Black
Energy efficiency rating Acoustic emissions (dB(A))*****		: В : 37
Electrical power (W)*** Electrical intensity (A)***		: 70 : 0.33
Consumption per 24h (KWh) **** Annual energy consumption AEc* (kWh/year) **** Ambient temperature operating limit		: 0.59 : 216 : 12 - 30°C

✓ Digital electronic controls with temperature setting range from 6°C to 10°C (lower cabinet area) and 15°C to 20°C (upper cabinet area)

- Temperature display on indoor sidewall
- ✓ Double Hot/ Cold circuit
- Temperature fault alarm icon
- ✓ Interior lining of dimpled aluminium
- ✓ Glass door
- ✓ Reversible door
- ✓ Integrated handle into the door frame
- ✓ Lock
- ✓ 2 adjustable feet
- ✓ Storage grid in the low part

www.artevino.fr - artevino@artevino.fr